





FUNI ACCIAIO ZINCATO ED INOX

INOX 049 AISI 316	Ø FUNE	FILO EXT.	PESO	CARICO ROTTURA min.	
				Kgf.	kN
49 fili – 7x7 Crociata DX – Res. 1.570 N/mm ²	mm.	mm.	Kg/m.		
	1,5	0,16	0,008	140	1,37
	2	0,22	0,014	250	2,45
	2,5	0,27	0,023	420	4,12
	3	0,32	0,035	520	5,10
	4	0,42	0,062	920	9,02
	6	0,64	0,142	2.100	20,59
	8	0,85	0,252	3.700	36,27

INOX 133 AISI 316	Ø FUNE	FILO EXT.	PESO	CARICO ROTTURA min.	
				Kgf.	kN
133 fili – 7x19 Crociata DX – Res. 1.960 N/mm ²	mm.	mm.	Kg/m.		
	3	0,20	0,039	630	6,18
	4	0,26	0,060	1.050	10,29
	5	0,33	0,085	1.540	15,10
	6	0,43	0,150	2.100	20,59
	7	0,45	0,187	2.700	26,47
	8	0,53	0,238	3.650	35,78
	10	1,10	0,375	6.020	59,02
	12				

ZT 519 R-TR	Ø FUNE	SEZ.MET.	PESO	CARICO ROTTURA min.	
				Kgf.	kN
5x19 – Croc DX – Res. 2.160 N/mm ²	mm.	mm.	Kg/m.		
	6	17,90	0,150	3.080	30,20
	8,3	29,90	0,260	5.538	54,29
	9,5	38,10	0,340	7.048	69,10
	10	43,10	0,380	7.976	78,20

FUNE RIVESTITA IN PVC	Ø int.	Ø ext.	COLORE	CARICO ROTTURA min.	
				Kgf.	kN
	1,5	2,1	NERO	204,00	2,00
	1,5	2,5	TRASP.	154,02	1,51
	3	4	TRASP.	612,00	6,00
	3	6	ROSSO	612,00	6,00