





FUNI ACCIAIO ZINCATO A 6 TREFOLI ANIMA METALLICA

ZM 719 133 fili – 7x19 Crociata DX – Res. 1.960 N/mm ²	Ø FUNE mm.	FILO EXT. mm.	PESO Kg/m.	CARICO ROTTURA min.	
				Kgf.	kN
	2	0,13	0,015	310	3,04
	3	0,20	0,035	615	6,03
	4	0,26	0,062	1.160	11,37
	4,8	0,30	0,088	1.900	18,63
	5	0,32	0,100	1.915	18,77
	6	0,40	0,150	2.600	25,49
	6,5	0,45	0,180	3.050	29,90
	7	0,47	0,210	3.615	35,44
	8	0,50	0,255	4.200	41,18
	9	0,60	0,310	5.300	51,96
10	0,65	0,381	6.800	66,67	

ZM 625 150 fili – 6x25+AM Crociata DX – Res. 1.960 N/mm ²	Ø FUNE mm.	FILO EXT. mm.	PESO Kg/m.	CARICO ROTTURA min.	
				Kgf.	kN
	6	0,38	0,150	2.700	26,47
	7	0,44	0,200	3.620	35,49
	8	0,50	0,250	4.750	46,57
	9	0,56	0,330	5.960	58,43
	10	0,64	0,410	7.600	74,51
	11	0,69	0,490	9.280	90,98
	12	0,75	0,580	10.900	106,86

ZM 625 R 150 fili – 6x25+AM Crociata DX – Res. 2.160 N/mm ²	Ø FUNE mm.	FILO EXT. mm.	PESO Kg/m.	CARICO ROTTURA min.	
				Kgf.	kN
	6	0,38	0,150	3.305	32,40
	7	0,44	0,200	4.010	39,31
	8	0,50	0,250	5.800	56,86
	9	0,56	0,330	7.400	72,55
	10	0,64	0,410	8.870	86,96
	11	0,69	0,490	10.100	99,02
	12	0,75	0,580	12.050	118,14

ZM 625 R-TR 150 fili – 6x25+AM – Trefoli Trafilati Crociata DX – Res. 2.160 N/mm ²	Ø FUNE mm.	FILO EXT. mm.	PESO Kg/m.	CARICO ROTTURA min.	
				Kgf.	kN
	6	0,52	0,175	3.600	35,29
	7	0,61	0,245	4.900	48,04
	8	0,68	0,300	6.200	60,78
	9	0,77	0,390	7.610	74,61
	10	0,84	0,477	9.500	93,14
	11	0,90	0,583	11.380	111,57
	12	1,00	0,703	13.400	131,37
	14	0,95	0,906	17.300	169,61