




FUNI ACCIAIO ZINCATO A 6 TREFOLI ANIMA METALLICA

ZM 636 216 fili – 6x36+AM Crociata DX – Res. 1.960 N/mm ²	Ø FUNE	FILO EXT.	PESO	CARICO ROTTURA min.	
	mm.	mm.	Kg/m.	Kgf.	kN
	10	0,55	0,418	6.700	65,69
	12	0,66	0,605	9.600	94,12
	14	0,77	0,800	12.800	125,49
	16	0,90	1,130	16.500	161,76
	18	1,00	1,330	20.900	204,90
	20	1,12	1,640	25.800	252,94
	22	1,23	1,980	31.300	306,86
	24	1,35	2,350	37.100	363,73
	26	1,46	2,770	43.500	426,47
	28	1,55	3,300	50.400	494,12
	30	1,66	3,750	60.000	588,24
	32	1,78	4,250	66.800	654,90

ZM 636 R 216 fili – 6x36+AM Crociata DX – Res. 2.160 N/mm ²	Ø FUNE	FILO EXT.	PESO	CARICO ROTTURA min.	
	mm.	mm.	Kg/m.	Kgf.	kN
	10	0,55	0,420	8.900	87,25
	11	0,62	0,520	10.160	99,61
	12	0,66	0,610	12.300	120,59
	13	0,72	0,700	14.200	139,22
	14	0,77	0,820	16.900	165,69
	15	0,84	0,960	18.870	185,00
	16	0,90	1,150	22.100	216,67
	17	0,94	1,230	24.260	237,84
	18	1,00	1,350	27.800	272,55
	19	1,07	1,530	31.000	303,92
	20	1,12	1,670	33.900	332,35
	22	1,23	2,020	41.000	401,96
	24	1,35	2,410	48.300	473,53
	26	1,46	2,830	56.600	554,90
	28	1,55	3,350	85.500	838,24
30	1,66	3,800	75.600	741,18	
32	1,78	4,350	86.000	843,14	

ZM 636 R-TR 216 fili – 6x36+AM – Tref. Trafilati Crociata DX – Res. 2.160 N/mm ²	Ø FUNE	FILO EXT.	PESO	CARICO ROTTURA min.	
	mm.	mm.	Kg/m.	Kgf.	kN
	14	0,75	0,820	18.100	177,45
	16	0,86	1,180	23.700	232,35
	18	0,98	1,370	30.100	295,10
	20	1,07	1,700	36.950	362,25
	22	1,19	2,050	44.870	439,90
	24	1,28	2,430	53.250	522,06
	26	1,38	2,850	62.620	613,92
	28	1,53	3,380	71.105	697,11
	30	1,64	3,850	81.450	798,53
	32	1,70	4,370	92.100	902,94